



SIMPLEX® CEILINGS

255 Montpelier, St. Laurent
(Montreal) QC, Canada H4N 2G3
Tel: (800) 638-5726 Fax (514) 744-2716
www.simplexceilings.com

Specifications

Lay-Away Series

- Panels:** Provide Simplex **Lay-Away** system manufactured from 0.032" (0,81mm) thick aluminum. Panel dimensions will be as shown on drawings. Panels are un-perforated or perforated with an un-perforated border, using pattern defined by the architect.
- Finish:** Select from Simplex Ceiling standards for panels. Custom colors available upon request.
- Suspension:** Suspension shall be 15/16" (24mm) Z-bar or T-Bar with standard mains tees.
- Perimeter:** Provide Lay-Away Mould with Hold down Clips as required in finish to match panels.
- Acoustical:** For perforated panels, provide a 0.008" (0.2mm) thick Simplex "T" non-woven acoustical textile to be bonded to the inside face of the panels. Can also be provided in 1-1/2" (38 mm) thick x 3/4 lb/cu.ft (12 kg/m³) density glass wool fiber completely sealed in an incombustible bag and installed with accordion pad spacers placed between the panel back and acoustical pad.

Standard Sizes: 24" x 24" 24" x 48"

Metric Sizes (mm): 610 x 610 610 x 1219

